

# AAT-725 SPORTS FLOOR AND RESILIENT ADHESIVE



2 part urethane yields very high shear & tensile strengths  
Great for heavy traffic and rolling loads  
Permanently waterproof formula  
Solvent free, 0 VOC, LEED qualified

- **Use For:** sport floor, synthetic turf and other resilient floor coverings
- **Recommended Trowels/Coverage:** Flat backings 1/16" x 1/16" x 1/16" V notch up to 180 sf/gal. • Rough backings 1/8" x 1/8" x 1/16" V notch up to 70 sf/gal. • Sport Flooring 3/32" x 3/32" x 3/32" V notch up to 135 sf/gal. • Outdoor on rough surface 3/16" x 3/16" x 3/16" V notch up to 50 sf/gal.
- **Sub-Floor Parameters:** *in situ* RH 100%/25#MVER
- **Packaging Size:** Part A - 2 gallon pails – 48 per pallet; Part B – 1.5qt 12/cs

# AAT-722 URETHANE LEVELING COMPOUND



Waterproof leveling compound  
Compressive strength > 14,500psi  
Apply from 1/32". No max thickness  
Cures in 4 hours or less

- **Use For:** high performance leveler for installations of a wide range of floorings over concrete slabs with very high moisture content.
- **Recommended Trowels/Coverage:** 5/32" x 1/8" V notch [sawtooth] up to 50 sf/gal. @ 1/32"
- **Sub-Floor Parameters:** No Max. as leveler. • Moisture Barrier: *in situ* RH 97%/18#MVER
- **Packaging Size:** Part A - 2 gallon pails – 48 per pallet; Part B – 1.75qt 12/cs

# AAT-420 PREMIUM VINYL PLANK AND LVT ADHESIVE



Advanced acrylic-ester professional formula  
Extremely aggressive "Dry Set"  
CRI GLP certified low VOC

- **Use For:** vinyl plank, LVT
- **Recommended Trowels/Coverage:** 1/16" x 1/32" x 1/32" U – up to 250 sf/gal
- **Sub-Floor Parameters:** *in situ* RH 95%/10#MVER
- **Packaging Size:** 4 gallon pails – 48 per pallet  
1 gallon pails – 4x1g/cs 42 cs per pallet

# AAT-620 PREMIUM PRESSURE SENSITIVE ADHESIVE



Multi-use ultra-aggressive PSA  
Fast tacking, long working time, re-bondable  
CRI GLP certified low VOC

- **Use For:** vinyl plank, LVT, carpet tile & F/G sheet vinyl
- **Recommended Trowels/Coverage:** 1/16" x 1/32" x 1/32" U – up to 250 sf/gal
- **Sub-Floor Parameters:** *in situ* RH 90%/8#MVER
- **Packaging Size:** 4 gallon pails – 48 per pallet;  
1 gallon pails – 4x1g/cs 42 cs per pallet

# AAT-275 ULTRA PREMIUM ADHESIVE



Use for heaviest commercial applications  
Ultra-strong bond, Superior re-tack  
Maximum extended working for Double Glue & pattern matching  
CRI GLP certified low VOC

- **Use For:** latex unitary, urethane attached cushion, woven polypropylene, hot melt, woven, polyurethane laminate and other commercial backings
- **Recommended Trowels/Coverage:** 1/8" x 1/8" x 1/8" U notch, 100 sf/gal • 3/32" x 3/32" x 3/32" V notch, 125 sf/gal • 1/8" x 1/8" x 1/16" U notch, 50 sf/gal
- **Sub-Floor Parameters:** *in situ* RH 90%/8#MVER
- **Packaging Size:** 4 gallon pails – 48 per pallet  
1 gallon pails – 4x1g/cs 42 cs per pallet

# AAT-270 ANCHOR BOND PREMIUM ADHESIVE



Premium performance and value  
Highly versatile, aggressive tacking adhesive for commercial applications  
CRI GLP certified low VOC

- **Use For:** latex unitary, urethane attached cushion, woven polypropylene, hot melt, woven, polyurethane laminate and other commercial backings
- **Recommended Trowels/Coverage:** 1/8" x 1/8" x 1/8" U notch, 100 sf/gal • 3/32" x 3/32" x 3/32" V notch, 125 sf/gal • 1/8" x 1/8" x 1/16" U notch, 50 sf/gal
- **Sub-Floor Parameters:** *in situ* RH 85%/8#MVER
- **Packaging Size:** 4 gallon pails – 48 per pallet



# AAT-560 PROFESSIONAL URETHANE WOOD FLOORING ADHESIVE



Industry leading shear strength  
Isocyanate free, easy cleaning urethane formula  
EC-1 Certified low VOC | 1 step moisture barrier

- **Use For:** eng. wood, solid wood; strip, plank, shorts and bamboo
- **Recommended Trowels/Coverage:** Eng. wood 3/16" X 1/4" x 5/16" V 50-60 - sf/gal ▪ Solid wood 3/16" x 3/16" x 3/16" Π notch – 30-40 sf/gal  
▪ Moisture barrier 1/8" x 5/32" x 3/16" x 5/64" V notch with pins – 30-35sf/gal
- **Packaging Size:** 3 gallon pails – 48 per pallet

# AAT-550 URETHANE WOOD FLOORING ADHESIVE



High solids, high strength formula  
Easy spreading, no slump formula  
Long working time, excellent green strength

- **Use For:** engineered wood, solid shorts, acoustical underlayment
- **Recommended Trowels/Coverage:** Eng. wood 3/16" X 1/4" x 5/16" V 50-60 - sf/gal ▪ Shorts 3/16" x 3/16" x 3/16" Π notch – 30-40 sf/gal ▪ Acoustical Underlayment 3/32" x 3/32" 3/32" V 100-110 sf/gal ▪ Moisture barrier 1/8" x 5/32" x 3/16" x 5/64" V notch with pins – 30-35sf/gal
- **Packaging Size:** 4 gallon pails – 36 per pallet

# AAT-570 ACRYLIC PRIMER



Primes and seals porous sub-floors  
Increases spread rate of new adhesive  
Provides an effective barrier from highly alkaline conditions  
Isolates existing adhesive residue

- **Use For:** priming gypsum cement and other highly porous sub-floors, enhancing adhesive performance, encapsulating adhesive residue.
- **Recommended Trowels/Coverage:** up to 350 sq.ft./gal per coat with a long nap roller
- **Packaging Size:** 4 gallon pails – 48 per pallet; 1 gallon pails – 4x1g/cs 42 cs per pallet

# AAT-432 ACRYLIC COVE BASE ADHESIVE



Superior "wet" bond strength for holding outside corners  
Superb final bond strength to minimize shrinkage  
Quick drying formula / 0 VOC [SCAQMD rule 1168]

- **Use For:** rubber, vinyl and carpet cove base
- **Coverage:** 2 1/2" base – up to 300 LF/gal; 4" base – up to 250 LF/gal ▪ 6" base – up to 160 LF/gal
- **Packaging Size:** 4 gallon pails – 48 per pallet  
1 gallon pails – 4x1g/cs 42 cs per pallet; 12x28FLOZ/cs 52 cs per pallet

